

Material Safety Data Sheet

Material Name: FLEXCO Flex-Tuft Adhesive

ID: SAH00360

*** Section 1 - Chemical Product and Company Identification ***

Material Name: FLEXCO Flex-Tuft Adhesive

Product Use

Adhesive

Manufactured For:

Flexco, Inc
1401 East 6th Street
Tuscumbia, AL 35674
Phone: 1-800-633-3151

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300

(Canada) CANUTEC 1-631-996-6666

*** Section 2 - Hazards Identification ***

Emergency Overview

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is irritating to the eyes.

Hazard Statements

CAUTION! IRRITANT. Irritating to eyes. Wear suitable gloves and eye/face protection. Keep out of the reach of children.

Potential Health Effects: Eyes

This product is irritating to the eyes.

Potential Health Effects: Skin

This product may cause irritation to the skin.

Potential Health Effects: Ingestion

Ingestion of this product may cause nausea, vomiting and diarrhea.

Potential Health Effects: Inhalation

This product may cause irritation to the respiratory system.

Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: Safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
1317-65-3	Limestone	10-30
64742-52-5	Naphthenic oil	10-30
1332-58-7	Kaolin	10-30
8050-09-7	Rosin	1-5

Material Safety Data Sheet

Material Name: FLEXCO Flex-Tuft Adhesive

ID: SAH00360

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a moderate fire hazard.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical (preferred), foam, water.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Personal Precautions

Wear appropriate protective equipment and clothing during clean-up.

Containment Procedures

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

Environmental Precautions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Keep out of the reach of children.

Evacuation Procedures

None identified.

Special Procedures

Regulations vary. Consult local authorities before disposal.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Avoid breathing vapors or mists of this product. Wash hands after handling and before eating. Keep out of the reach of children.

Material Safety Data Sheet

Material Name: FLEXCO Flex-Tuft Adhesive

ID: SAH00360

Storage Procedures

Store in a cool, dry, well-ventilated area. Store at ambient temperature and atmospheric pressure. Keep out of sun.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

Limestone (1317-65-3)

OSHA (Final):	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction
NIOSH:	10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust
Alberta:	10 mg/m3 TWA
British Columbia:	10 mg/m3 TWA total dust; 3 mg/m3 TWA respirable fraction 20 mg/m3 STEL total dust
New Brunswick:	10 mg/m3 TWA particulate matter containing no asbestos and < 1% crystalline silica
NW Territories:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Nunavut:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Quebec:	10 mg/m3 TWAEV total dust, containing no asbestos and less than 1% crystalline silica
Saskatchewan:	10 mg/m3 TWA 20 mg/m3 STEL
Yukon:	30 mppcf TWA; 10 mg/m3 TWA 20 mg/m3 STEL

Kaolin (1332-58-7)

ACGIH:	2 mg/m3 TWA respirable fraction, particulate matter containing no asbestos and <1% crystalline silica
OSHA (Final):	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction
NIOSH:	10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust
Alberta:	2 mg/m3 TWA (respirable)
British Columbia:	2 mg/m3 TWA particulate matter containing no asbestos and less than 1% crystalline silica
Manitoba:	2 mg/m3 TWA respirable fraction particulate matter containing no asbestos and <1% crystalline silica
New Brunswick:	2 mg/m3 TWA particulate matter containing no asbestos and < 1% crystalline silica, respirable fraction
NW Territories:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Nova Scotia:	2 mg/m3 TWA respirable fraction, particulate matter containing no asbestos and <1% crystalline silica
Nunavut:	5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass
Ontario:	2 mg/m3 TWAEV respirable containing no asbestos and less than 1% crystalline silica
Quebec:	5 mg/m3 TWAEV respirable dust, containing no asbestos and less than 1% crystalline silica
Saskatchewan:	2 mg/m3 TWA (respirable fraction) 4 mg/m3 STEL (respirable fraction)
Yukon:	30 mppcf TWA; 10 mg/m3 TWA 20 mg/m3 STEL

Rosin (8050-09-7)

British Columbia:	Sensitizer; Exposure by all routes should be carefully controlled to levels as low as possible
Quebec:	0.1 mg/m3 TWAEV formaldehyde

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Local exhaust is suggested for use, where possible, in enclosed or confined spaces.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

Personal Protective Equipment: Respiratory

Not normally needed. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Personal Protective Equipment: General

Laundry contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

Material Safety Data Sheet

Material Name: FLEXCO Flex-Tuft Adhesive

ID: SAH00360

*** Section 9 - Physical & Chemical Properties ***

Appearance:	Beige paste	Odor:	Slight odor
Physical State:	Paste	pH:	N/A
Vapor Pressure:	N/A	Vapor Density:	Heavier than air
Boiling Point:	212° F	Melting Point:	N/A
Solubility (H2O):	N/A	Specific Gravity:	1.30
Evaporation Rate:	Slower than ether	VOC:	17 g/L
Octanol/H2O Coeff.:	N/A	Flash Point:	N/A
Flash Point Method:	N/A	Upper Flammability Limit (UFL):	N/A
Lower Flammability Limit (LFL):	N/A	Burning Rate:	N/A
Auto Ignition:	N/A		

Physical Properties: Additional Information

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Do not freeze.

Incompatibility

This product may react with strong acids, bases and oxidizing agents.

Hazardous Decomposition

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

No information available for the product.

B: Component Analysis - LD50/LC50

Naphthenic oil (64742-52-5)

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

Rosin (8050-09-7)

Oral LD50 Rat 3 mg/kg; Dermal LD50 Rabbit >2500 mg/kg

Carcinogenicity

A: General Product Information

No information available for the product.

B: Component Carcinogenicity

Kaolin (1332-58-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Material Safety Data Sheet

Material Name: FLEXCO Flex-Tuft Adhesive

ID: SAH00360

Sensitization

No information available for the product.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Naphthenic oil (64742-52-5)

Test & Species		Conditions
96 Hr LC50 Oncorhynchus mykiss	>5000 mg/L	
48 Hr EC50 Daphnia magna	>1000 mg/L	

Rosin (8050-09-7)

Test & Species		Conditions
72 Hr EC50 Desmodemus subspicatus	400 mg/L	
48 Hr EC50 Daphnia magna	3.8 - 5.4 mg/L	

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

No additional information available.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

*** Section 14 - Transportation Information ***

International Transportation Regulations

Not regulated as dangerous goods.

*** Section 15 - Regulatory Information ***

US Federal Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

B: Component Analysis

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes	Yes
Kaolin	1332-58-7	No	Yes	Yes	Yes	Yes	Yes
Rosin	8050-09-7	No	No	Yes	No	No	No

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):
WARNING! This product contains a chemical known to the state of California to cause cancer.

Material Safety Data Sheet

Material Name: FLEXCO Flex-Tuft Adhesive

ID: SAH00360

Canadian WHMIS Information

A: General Product Information



B: Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

Additional Regulatory Information

A: General Product Information

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Limestone	1317-65-3	Yes	NDSL	EINECS
Naphthenic oil	64742-52-5	Yes	DSL	EINECS
Kaolin	1332-58-7	Yes	DSL	EINECS
Rosin	8050-09-7	Yes	DSL	EINECS

* * * Section 16 - Other Information * * *

Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Key/Legend

NA = Not available or Not Applicable. ACGIH = American Conference of Governmental Industrial Hygienists. NFPA = National Fire Protection Association. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist

Contact Phone: 1-954-246-8888

End of Sheet SAH00360