

# FlexTuft Vulcanized and Non-Vulcanized Rubber Tile Maintenance

## COMPANY INFORMATION

Flexco Corporation  
1401 East 6<sup>th</sup> Street  
Tuscumbia, AL, USA 35674  
Telephone: (256) 383-7474; (800) 633-3151  
Facsimile: (256) 381-0322; (800) 346-9075  
Email: [info@flexcofloors.com](mailto:info@flexcofloors.com), [technical@flexcofloors.com](mailto:technical@flexcofloors.com)  
Internet: [www.flexcofloors.com](http://www.flexcofloors.com)  
Sweet's Catalog: 09650/FLE; Buyline 0254; [www.sweets.com](http://www.sweets.com)

## PRODUCT MAINTENANCE

### 1. Initial Maintenance

Properly clean the flooring before releasing for its normal use. **DO NOT** perform any maintenance or allow the product to be exposed to water, rain, cleaning agents, or other materials for at least 72 hours after installation to allow the adhesive to properly cure. Remove any covering used to protect the floor after installation prior to use. Sweep and / or vacuum with a high CFM vacuum to remove dirt and other particulate. Spot clean or shampoo with a neutral pH cleaner or a mild soap and water solution to remove any stains.

### 2. Routine Maintenance

Properly cleaning FlexTuft at a minimum of a weekly basis will help to maximize the life of the product. Sand, grit and grime on the surface of the tiles can become very abrasive and reduce the life of the product. Cleaning schedules should be adjusted based on traffic and location of the FlexTuft.

#### 2.1 Interior Applications

Sweep, vacuum, spot clean or shampoo Interior applications for cleaning. Use a neutral pH cleaning solution or a mild soap and water solution for spot cleaning or shampooing. Immediately remove all spills from the flooring when noticed, failure to do this can lead to greater staining. **DO NOT** use highly alkaline cleaners, highly acidic cleaners, or sweeping compounds containing oils or solvents. **DO NOT** allow cleaning solutions or other chemicals that could deteriorate the adhesive to stand on the flooring.

#### 2.2 Exterior Applications

Hose, Sweep, vacuum, spot clean or shampoo Exterior applications for cleaning. Use a neutral pH cleaning solution or a mild soap and water solution for spot cleaning or shampooing. Immediately remove all spills from the flooring when noticed, failure to do this can lead to greater staining. Tiles can be left to dry naturally. **DO NOT** use highly alkaline cleaners, highly acidic cleaners, or sweeping compounds containing oils or solvents. **DO NOT** allow cleaning solutions or other chemicals that could deteriorate the adhesive to stand on the flooring.