

Flexco 106 Wall Base Adhesive

DESCRIPTION

Flexco 106 Wall Base Adhesive is a premium solvent free Acrylic adhesive with aggressive wet suction grip for all Flexco Wall Base products. Flexco 106 Wall Base Adhesive can be used over most interior wall surfaces with proper techniques, contact technical services for applications over vinyl wall coverings. Antimicrobial protection is formulated into the product during manufacturing to continuously inhibit the growth of bacteria, mildew and mold that can cause stains and odors.

COLOR

Off-White to Cream

PACKAGING

30 Ounce Cartridges, 12 Cartridges per Case
1 Gallon Plastic Pails, 4 Pails per Case
4 Gallon Plastic Pails

WEIGHT

30 Pounds per Cartridge Cases
10 Pounds per Gallon Unit
40 Pounds per 4 Gallon Unit

TROWEL SIZES

Disposable Spreader Nozzle
1/8" x 1/8" x 1/8" V-Notch Spreader

COVERAGES

Approximately 150 – 200 Linear Feet per Gallon

RECOMMENDED SUBSTRATES

Most properly prepared interior substrates, Contact Technical Services if questions

ADHESIVE WORKING TIME

Flash Time: 5-10 Minutes

Working Time: 45 Minutes

MOISTURE AND PH REQUIREMENTS

N/A

PRODUCTS

Flexco Wallflowers Wall Base, Base 2000 Wall Base, Base Sculptures, Health Design Coving, Wood Elements Wall Base, Vinyl Wall Base

CLEAN UP

Remove any wet adhesive immediately with a soft clean cloth with warm soapy water. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol or mineral spirits.

CALCULATED VOCs

Compliant, per SCAQMD Rule #1168
< 1 Gram / Liter of Material & Coating, per SCAQMD Rule #443.1

LIMITATIONS

Not for use over existing floor covering or old adhesives
Not for use outdoors

SHELF LIFE

Shelf life is one year when stored at 70° F (21° C) in an unopened container

FREEZE THAW STABILITY

Material is Freeze Thaw Stable, up to five (5) cycles. Completely mix after frozen only after complete thawing.

QUALIFICATIONS

CRI Green Label Plus, CHPS and LEED Compliant

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from www.flexcofloors.com by clicking the Technical Support link, emailing installhelp@flexcofloors.com, or by contacting Flexco Customer Service @ 800-633-3131.

COMPANY INFORMATION

Flexco Corporation
1401 East 6th Street
Tuscumbia, AL, USA 35674
Phone: (256) 383-7474; (800) 633-3151
Email: info@flexcofloors.com, technical@flexcofloors.com.