

# Flexco 220 Sports Flooring Adhesive

## DESCRIPTION

Flexco 220 Sports Flooring Adhesive is an extremely low-odor formulation with negligible VOC content adhesive for Flexco Sports Flooring products. It is easy to trowel, 100% solids and solvent-free adhesive that utilizes rapidly renewable resources for raw materials.

## COLOR

Tan

## PACKAGING

2.5 Gallon Metal Pails  
5 Gallon Metal Pails

## WEIGHT

38 Pounds per 2.5 Gallon Pail  
74 Pounds per 5 Gallon Pail

## MIXING

Ready to use; no mixing required

## TROWEL SIZE

1/16" x 1/16" x 1/16", Square Notch



## COVERAGE

125 – 185 Square Feet per Gallon  
310 – 460 Square Feet per 2.5 Gallon Pail  
625 – 925 Square Feet per 5 Gallon Pail

## RECOMMENDED SUBSTRATES

Recommended for properly prepared Concrete, Terrazzo, Ceramic Tile, Wood and Cement-based self-leveling underlayments and patching compounds

## ADHESIVE WORKING TIME

Flash Time: 0-5 Minutes

Working Time: 45 Minutes

## MOISTURE AND PH REQUIREMENTS

ASTM F 1869; Calcium Chloride, 5.0 lbs  
ASTM F 2170; Relative Humidity, 75%  
pH; 11 or less

## PRODUCTS

Flexco Tuflex Force, Prime Sports Floor

## CLEAN UP

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water or mineral spirits, while the adhesive is still wet. 220 Sports Flooring Adhesive is extremely difficult to remove when cured

## VOCs

44 Grams per Liter, per SCAQMD Rule #1168

## LIMITATIONS

Light Traffic, 12 Hours  
Heavy Traffic & Rolling Loads, 24 Hours  
Maintenance; 48 Hours  
Equipment Installation; 72 Hours  
Not for use over existing floor covering or old adhesives  
Not for use outdoors

## SHELF LIFE

Shelf life is one year when stored at 70° F (21° C) in an unopened container

## FREEZE THAW STABILITY

Protect material from freezing. If frozen, do not stir until material has completely thawed

## QUALIFICATIONS

LEED Compliant

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from [www.flexcofloors.com](http://www.flexcofloors.com) by clicking the Technical Support link, emailing [installhelp@flexcofloors.com](mailto:installhelp@flexcofloors.com), or by contacting Flexco Customer Service @ 800-633-3131.

## COMPANY INFORMATION

Flexco Corporation  
1401 East 6<sup>th</sup> Street  
Tuscumbia, AL, USA 35674  
Phone: (256) 383-7474; (800) 633-3151  
Email: [info@flexcofloors.com](mailto:info@flexcofloors.com), [technical@flexcofloors.com](mailto:technical@flexcofloors.com)