

# Flexco FlexTuft Adhesive

## DESCRIPTION

Flexco FlexTuft Adhesive is a single-component, waterproof, synthetic rubber based adhesive designed for use with indoor and outdoor installations over porous and non-porous substrates. This adhesive contains antimicrobial protection that protects the dried/applied adhesive from mold, mildew and bacteria that cause odors and product degradation.

## COLOR

Cream Buff

## PACKAGING


1 Gallon Plastic Pails, 4 Pails per Case  
4 Gallon Plastic Pails

## WEIGHT

10 Pounds per Gallon Unit  
40 Pounds per 4 Gallon Unit

## TROWEL SIZES

Smooth Porous & Non-Porous Surfaces, 1/8" x 1/8" x 1/8" Square Notch Trowel



Rough Porous Surfaces, 3/16" x 3/16" x 3/16" Square Notch Trowel



## COVERAGES

Approximately 75 Square Feet per Gallon, 1/8" Square Notch Trowel on Smooth Porous Surfaces

## RECOMMENDED SUBSTRATES

Recommended for properly prepared Concrete and Wood

## ADHESIVE WORKING TIME

Flash Time: Approximately 15-20 Minutes or until material strings when touched

Working Time: 45 Minutes

## MOISTURE AND PH REQUIREMENTS

ASTM F 1869; Calcium Chloride, 8.0 lbs  
ASTM F 2170; Relative Humidity, 90%  
pH; 9 or less

## PRODUCTS

Flexco Vulcanized FlexTuft & Non-Vulcanized FlexTuft

## CLEAN UP

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water, while the adhesive is still wet. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol.

## CALCULATED VOCs

17 Grams per Liter of Coating, per SCAQMD Rule #1168

## LIMITATIONS

Foot traffic after 24 hours  
Light rolling loads after 48 hours  
Heavy rolling loads after 72 hours  
Maintenance after 48 hours

Not for use over existing floor covering or old adhesives

## SHELF LIFE

Shelf life is one (1) year when stored at 70° F (21° C) in an unopened container

## FREEZE THAW STABILITY

Material is Freeze Thaw Stable above 10° F (-12° C). Completely mix after frozen only after complete thawing.

## QUALIFICATIONS

CRI Green Label Plus, CHPS and LEED Compliant

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheet, Installation and/or Maintenance Instructions for additional detailed information. Obtain from [www.flexcofloors.com](http://www.flexcofloors.com) by clicking the Technical Support link, emailing [installhelp@flexcofloors.com](mailto:installhelp@flexcofloors.com), or by contacting Flexco Customer Service @ 800-633-3131.

## COMPANY INFORMATION

Flexco Corporation  
1401 East 6<sup>th</sup> Street  
Tuscumbia, AL, USA 35674  
Phone: (256) 383-7474; (800) 633-3151  
Email: [technical@flexcofloors.com](mailto:technical@flexcofloors.com), [installhelp@flexcofloors.com](mailto:installhelp@flexcofloors.com)