

Flexco Spray-Grip™ Adhesive for Vinyl Tile

DESCRIPTION

Flexco Spray-Grip™ Adhesive for Vinyl Tile is a no VOC, non-flammable water based adhesive formulated for use with Flexco Vinyl and Laminate Tiles. The immediate high sheer strength allows for foot traffic after installation and eliminates the worry of adhesive displacement due to early traffic. Spray-Grip Adhesive for Vinyl Tile reduces the amount of adhesive on projects by up to 80%, therefore reducing the amount of weight during shipment and manufacturing. Spray-Grip Adhesive for Vinyl Tile canisters are completely recyclable and the design allows for the complete use of the contents, so there is no waste.

COLOR

White

PACKAGING

22 ounce Aluminum Cans, 6 Cans per Case with Hand Lever and extra tips

WEIGHT

12 Pounds per Case

TROWEL SIZE

No Trowel Needed

COVERAGE

150 – 185 Square Feet per Can

RECOMMENDED SUBSTRATES

Recommended for properly prepared Concrete, Wood, Metal and Fiberglass

ADHESIVE WORKING TIME

Flash Time: Allow material to dry until there is no transfer to the finger when touched

Working Time: 4 hours, protect from contamination from dust

MOISTURE AND PH REQUIREMENTS

ASTM F 1869; Calcium Chloride, 7.0 lbs

ASTM F 2170; Relative Humidity, 85%

pH; 11 or less

PRODUCTS

Flexco Natural Elements Premium Wood Vinyl Plank, Natural Elements Luxury Vinyl Stone Tile, WoodTones Premium Wood Vinyl Plank, Health Design Vinyl Tile, Contract Vinyl Tile and Appeal Vinyl Tile

CLEAN UP

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water, while the adhesive is still wet. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol.

CALCULATED VOCs

0 Grams per Liter of Coating

LIMITATIONS

All Traffic, Immediately
Heat Welding, After 3 Hours
Maintenance, after 48 Hours

Not for use over existing floor covering or old adhesives
Not for use outdoors

SHELF LIFE

Shelf life is two years when stored at 70° F (21° C) in an unopened container

FREEZE THAW STABILITY

Protect material from freezing

QUALIFICATIONS

FloorScore, CHPS and LEED Compliant

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from www.flexcofloors.com by clicking the Technical Support link, emailing installhelp@flexcofloors.com, or by contacting Flexco Customer Service @ 800-633-3131.

COMPANY INFORMATION

Flexco Corporation
1401 East 6th Street
Tuscumbia, AL, USA 35674
Phone: (256) 383-7474; (800) 633-3151
Email: info@flexcofloors.com, technical@flexcofloors.com

