

1. PRODUCT NAME

Base Sculptures™ Wall Base

2. COMPANY INFORMATION

Flexco Corporation
1401 East 6th Street
Tuscumbia, AL, USA 35674
Phone: (256) 383-7474; (800) 633-3151
Fax: (256) 381-0322; (800) 346-9075
Email: info@flexcofloors.com, technical@flexcofloors.com
Internet: www.flexcofloors.com

3. PRODUCT DESCRIPTION

3.1 Basic Application and Construction

Flexco Base Sculptures Thermoplastic Rubber Wall Base is designed to produce a solid, durable, dimensionally stable thermoplastic rubber wall base for indoor use in commercial and residential applications. Base Sculptures Wall Base is extruded with an extremely tough finish to resist scratching, scuffing, and gouging. The unique compound provides outstanding flexibility for fast and economical installations. The surface texture is an appealing unique matte finish to ensure an attractive juncture of floors and walls. Contact Flexco or see www.flexcofloors.com for the latest color selections.

3.2 Product Types

Styles: Sculpted (Style D)
Gauge: 3/8" (9.2 mm) at base on 2 5/8" & 4 1/2", 1/4" (6.4 mm) at base on 7 3/4"
Heights: 2 5/8" (6.68 cm), 4 1/2" (11.43 cm), & 7 3/4" (19.69 cm)
Lengths: 40' (12.19 m) rolls; 40 linear feet (12.19 m) per carton

3.3 Corners

Flexco offers inside and outside corner blocks or Pre-Mitered inside and outside corners with a nominal 6" return. Form corners on the jobsite using standard woodworking methods and tools for a professional finish.

4. TECHNICAL DATA

ASTM F 1861 - Type TP, Group 1, Style D
ASTM E 84 (NFPA 255) - Class C
ASTM E 648 (NFPA 253) - Class 1
ASTM E 662 (NFPA 258) - Passes

5. PRODUCT LIMITATIONS

This product is for indoor use only. Do not install wall base on any surface exposed to moisture or extreme temperature changes. Fading can occur from extensive exposure to heavy direct or glass-filtered sunlight, or unfiltered ultra-violet rays. Base Sculptures must be installed using Flexco 106 Wall Base Adhesive and in accordance with Flexco's recommendations in order for the product warranty to be in effect. Other adhesives can lead to plasticizer migration, which will cause material to release from the substrate.

6. INSTALLATION

6.1 General Preparation and Conditioning

Allow all trades to complete work prior to installation of Flexco Base Sculptures Wall Base. Deliver all materials to the installation location in its original packaging with labels intact. Maintain the installation area, wall base, and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation.

6.2 Wall Surface Inspection

Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood (Group 1, CC type), concrete and masonry that is clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, non-porous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Follow the manufacturer's recommendations for any patching materials.

6.3 Adhesive Information

Flexco 106 Wall Base Adhesive

- Apply with 1/8" square notch trowel, adhesive spreader or disposable nozzle
- Coverage: approximately 175 linear feet of 4" Base Sculptures Wall Base
- Contains Anti-Microbial Protection
- VOC's: < 1 g/L of material & Coating

7. PRODUCT MAINTENANCE

Some disinfectants, cleaning agents, floor maintenance products and pesticides may stain or damage the surface of the Base Sculptures Wall Base. Clean the Base Sculptures Wall Base with a soft cloth dampened with a neutral pH cleaner and warm water solution. Rinse sparingly with water. If applying finish to flooring, take necessary precautions to keep finish from the Base Sculptures Wall Base. If applying finish to the Base Sculptures Wall Base, test inconspicuous area first for compatibility.

8. SAMPLES

Obtain Samples calling Flexco Customer Service or by visiting www.flexcofloors.com.

9. AVAILABILITY AND COST

Products are available through Flexco distributors. Contact Flexco Customer Service or visit www.flexcofloors.com for a list of distributors.

10. LIMITED WARRANTY

Limited One (1) Year Warranty

Refer to Flexco Base Sculptures Wall Base Installation or Maintenance documentation for any additional detailed information.

www.flexcofloors.com/technicalsupport/index.html

