

1. PRODUCT NAME**Vinyl Wall Base****2. COMPANY INFORMATION**

Flexco Corporation

1401 East 6th Street

Tuscumbia, AL, USA 35674

Phone: (256) 383-7474; (800) 633-3151

Fax: (256) 381-0322; (800) 346-9075

Email: info@flexcofloors.com, technical@flexcofloors.comInternet: www.flexcofloors.com**3. PRODUCT DESCRIPTION****3.1 Basic Application and Construction**

Flexco Vinyl Wall Base is extruded with a tough surface to resist scuffing, but has the flexibility for fast and economical installations and conceals floor and wall irregularities. The color is homogeneous throughout the entire thickness of the wall base. The surface texture is an appealing slick finish to ensure an attractive juncture of floors and walls. Contact Flexco or see www.flexcofloors.com for the latest color selections.

3.2 Product Types

Styles: Straight (Style A), Cove (Style B)

Gauge: 1/8" (3.175 mm) and 0.080" (2.03 mm)

Heights: 2 1/2" (6.35 cm), 4" (10.16 cm) & 6" (15.24 cm)

Lengths: 48" sections (1.22 m) & 120' (36.58 m) rolls; 120 linear feet (36.58 m) per carton

3.3 Corners

Preformed corners are available in 2 1/2" Inside and Outside, 4" Inside and Outside, 4 1/2" Outside and 6" Outside with a nominal 3" return.

4. TECHNICAL DATA

ASTM F 1861 - Type TV, Group 1, Styles A & B

ASTM E 84 (NFPA 255) - Class C

ASTM E 648 (NFPA 253) - Class 1

ASTM E 662 (NFPA 258) - Passes

5. PRODUCT LIMITATIONS

This product is for indoor use only. Do not install wall base on any surface exposed to moisture or extreme temperature changes. Fading can occur from extensive exposure to heavy direct or glass-filtered sunlight, or unfiltered ultra-violet rays. Vinyl Wall Base must be installed using Flexco 106 Wall Base Adhesive and in accordance with Flexco's recommendations in order for the product warranty to be in effect.

6. INSTALLATION**6.1 General Preparation and Conditioning**

Allow all trades to complete work prior to installation of Flexco Vinyl Wall Base. Deliver all materials to the installation location in its original packaging with labels intact. Maintain the installation area, wall base, and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation.

6.2 Wall Surface Inspection

Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood (Group 1, CC type), concrete and masonry that is clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, non-porous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Follow the manufacturer's recommendations for any patching materials.

6.3 Adhesive Information**Flexco 106 Wall Base Adhesive**

- Apply with 1/8" square notch trowel, adhesive spreader or disposable nozzle
- Coverage: approximately 200 linear feet of 4" Vinyl Wall Base
- Contains Anti-Microbial Protection
- VOC's: < 1 g/L of material & Coating

7. PRODUCT MAINTENANCE

Some disinfectants, cleaning agents, floor maintenance products and pesticides may stain or damage the surface of the Vinyl Wall Base. Clean the Vinyl Wall Base with a soft cloth dampened with a neutral pH cleaner and warm water solution. Rinse sparingly with water. If applying finish to flooring, take necessary precautions to keep finish from the Vinyl Wall Base. If applying finish to the Vinyl Wall Base, test inconspicuous area first for compatibility.

8. SAMPLES

Obtain Samples calling Flexco Customer Service or by visiting www.flexcofloors.com.

9. AVAILABILITY AND COST

Products are available through Flexco distributors. Contact Flexco Customer Service or visit www.flexcofloors.com for a list of distributors.

10. LIMITED WARRANTY

Limited One (1) Year Warranty

Refer to Flexco Vinyl Wall Base Installation or Maintenance documentation for any additional detailed information.

www.flexcofloors.com/technicalsupport/index.html

