

## 1. PRODUCT NAME

### Wood Elements Wall Base

## 2. COMPANY INFORMATION

Flexco Corporation  
1401 East 6<sup>th</sup> Street  
Tuscumbia, AL, USA 35674  
Phone: (256) 383-7474; (800) 633-3151  
Fax: (256) 381-0322; (800) 346-9075  
Email: [info@flexcofloors.com](mailto:info@flexcofloors.com), [technical@flexcofloors.com](mailto:technical@flexcofloors.com)  
Internet: [www.flexcofloors.com](http://www.flexcofloors.com)

## 3. PRODUCT DESCRIPTION

### 3.1 Basic Application and Construction

Flexco Wood Elements Thermoplastic Rubber Wall Base is designed to produce a solid, durable, dimensionally stable laminated thermoplastic rubber wall base for indoor use in commercial and residential applications. Wood Elements Wall Base is laminated with an extremely tough print film to resist scratching, scuffing, and “whiting out” when bent for corners. The unique base ply compound provides outstanding flexibility and hand for fast and economical installations. Contact Flexco or see [www.flexcofloors.com](http://www.flexcofloors.com) for the latest color selections.

### 3.2 Product Types

Styles: Cove (Style B)  
Gauge: 1/8” (3.175 mm)  
Heights: 4” (10.16 cm)  
Lengths: 48” sections (1.22 m) & 120’ (36.58 m) rolls; 120 linear feet (36.58 m) per carton

### 3.3 Corners

Preformed inside and outside corners are available with a nominal 3” return

## 4. TECHNICAL DATA

ASTM F 1861 - Type TP, Group 2, Style B  
ASTM E 84 (NFPA 255) - Class C  
ASTM E 648 (NFPA 253) - Class 1  
ASTM E 662 (NFPA 258) - Passes

## 5. PRODUCT LIMITATIONS

This product is for indoor use only. Do not install wall base on any surface exposed to moisture or extreme temperature changes. Fading can occur from extensive exposure to heavy direct or glass-filtered sunlight, or unfiltered ultra-violet rays. Wood Elements Wall Base must be installed using Flexco 106 Wall Base Adhesive and in accordance with Flexco’s recommendations in order for the product warranty to be in effect.

## 6. INSTALLATION

### 6.1 General Preparation and Conditioning

Allow all trades to complete work prior to installation of Flexco Wood Elements Wall Base. Deliver all materials to the installation location in its original packaging with labels intact. Maintain the installation area, wall base, and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation.

### 6.2 Wall Surface Inspection

Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood (Group 1, CC type), concrete and masonry that is clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, non-porous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Follow the manufacturer’s recommendations for any patching materials.

### 6.3 Adhesive Information

#### Flexco 106 Wall Base Adhesive

- Apply with 1/8” square notch trowel, adhesive spreader or disposable nozzle
- Coverage: approximately 200 linear feet of 4” Wood Elements Wall Base
- Contains Anti-Microbial Protection
- VOC’s: < 1 g/L of material & Coating

## 7. PRODUCT MAINTENANCE

Some disinfectants, cleaning agents, floor maintenance products and pesticides may stain or damage the surface of the Wood Elements Wall Base. Clean the Wood Elements Wall Base with a soft cloth dampened with a neutral pH cleaner and warm water solution. Rinse sparingly with water. If applying finish to flooring, take necessary precautions to keep finish from the Wood Elements Wall Base. If applying finish to the Wood Elements Wall Base, test inconspicuous area first for compatibility.

## 8. SAMPLES

Obtain Samples calling Flexco Customer Service or by visiting [www.flexcofloors.com](http://www.flexcofloors.com).

## 9. AVAILABILITY AND COST

Products are available through Flexco distributors. Contact Flexco Customer Service or visit [www.flexcofloors.com](http://www.flexcofloors.com) for a list of distributors.

## 10. LIMITED WARRANTY

Limited One (1) Year Warranty

Refer to Flexco Wood Elements Wall Base Installation or Maintenance documentation for any additional detailed information.

[www.flexcofloors.com/technicalsupport/index.html](http://www.flexcofloors.com/technicalsupport/index.html)

