

1. PRODUCT NAME

WoodTones™ Premium Wood Vinyl Plank

2. COMPANY INFORMATION

Flexco Corporation
1401 East 6th Street
Tuscumbia, AL, USA 35674
Phone: (256) 383-7474; (800) 633-3151
Fax: (256) 381-0322; (800) 346-9075
Email: info@flexcofloors.com, technical@flexcofloors.com
Internet: www.flexcofloors.com

3. PRODUCT DESCRIPTION

3.1 Basic Application and Construction

Flexco WoodTones Premium Wood Vinyl Plank is designed for use in commercial and residential applications. The WoodTones Premium Wood Vinyl Plank collection features a natural wood look. The pure virgin vinyl formulation provides excellent resistance to abrasion, chipping, cracking, and permanent indentations for heavy-duty performance requirements and to help conceal most substrate irregularities, and yet it is flexible for fast and economical installations. It's rugged construction, including a 0.040" wear layer, permits maximum durability ensuring long lasting beauty without the use of a floor finish. WoodTones Premium Wood Vinyl Plank is the perfect choice for lobbies, office buildings, banks, healthcare facilities, luxurious residential and commercial condominiums, or wherever both function and high design are essential to provide the effect of elegant polished wood. The surface includes an embossed surface to enhance the rich look of wood, while adding slip resistance qualities to the tile. Precision cutting allows for easy installation with tight seams. WoodTones Premium Wood Vinyl Plank is available in straight or beveled edges. Contact Flexco or see www.flexcofloors.com for the latest color selections.

3.2 Product Types

WoodTones Premium Wood Vinyl Plank – Straight Edge & Beveled Edge

- Gauge: 1/8" (3.175 mm)
- Size: 3" (76.2 mm) x 36" (914.4 mm)

4. TECHNICAL DATA

ASTM F 1700 - Solid Vinyl Tile; Class III, Type B
ASTM E 648 (NFPA 253), **Critical Radiant Flux** - Class 1
ASTM E 662 (NFPA 258), **Smoke Density** - Passes
ASTM F 925, **Chemical Resistance** - Passes
ASTM D 2047, **Slip Resistance** - > 0.50
ASTM F 970, **Static Load** - 250 PSI; Modified 300 PSI
ASTM F 1515, **Light Stability** - Passes
ASTM F 3389, **Abrasion Resistance** - Excellent
ASTM G 21 - Excellent Resistance

5. PRODUCT LIMITATIONS

- Must be installed using Flexco Spray-Grip for Vinyl, Flexco 16/86 Multi-Performance Tile & Tread Adhesive, or Flexco 77 Solvent-Free Epoxy Adhesive
- Flexco does not recommend the use of floor finishes, sealers or waxes of any kind, maintain desired sheen and shine through maintenance procedures
- May stain if allowed to remain in contact with products that contain staining ingredients such as tires, casters, and walk-off mats

- Ensure that any disinfectant, cleaning agent, dye, pesticide, or other chemical (solid, liquid, or gas) that may come in contact with the flooring will not produce permanent discoloration and/or damage to the flooring
- Not to be used in or near commercial kitchens or other areas exposed to animal fats, greases, oils, solvents, strong detergents or where there is excessive moisture
- Not to be used in areas that may be subjected to sharp spikes, cleats, sharp wheels, or other objects that could damage the flooring
- Use appropriate floor protection devices, dragging or improperly moving furniture or equipment across the surface of the tile or dropping objects onto the surface of the tile may cause permanent damage to the flooring
- Not to be used in direct contact with heat sources, such as radiators, hot ovens or other heated equipment
- Not to be used in outdoor applications

6. INSTALLTION

6.1 General Preparation and Conditioning

- Allow all trades to complete work prior to installation of Flexco WoodTones Premium Wood Vinyl Plank
- Deliver all materials to the installation location in its original packaging with labels intact
- Remove any plastic stretch wrap and strapping from product after delivery to jobsite
- Do not stack pallets of material to avoid any damage
- Maintain the installation area, tile and adhesive between 65° F (19° C) and 85° F (30° C) for at least 48 hours before installation, during installation, and after the installation
- Remove material from cartons and stack evenly on a smooth dry surface no more than 18" high
- Inspect all material for proper type and color
- Conduct the proper moisture emission and pH testing on the substrate

6.2 Substrate Inspection and Preparation

Inspect all substrates prior to installation. All substrates must be clean, smooth, permanently dry, flat, and structurally sound. The substrate must be free of moisture, dust, sealers, paint, curing compounds, parting agents, residual adhesives, adhesive removers, hardeners, resinous compounds, solvents, wax, oil, grease, asphalt, gypsum compounds, alkaline salts, excessive carbonation or laitance, mold, mildew, any other extraneous coatings, films, materials and all other foreign matter which might interfere/restrict proper adhesive bonding. In renovation or remodel work, remove all existing adhesive residue so that 100% of the overall area of the original subfloor/substrate is exposed.

6.3 Adhesive Information

Flexco Spray-Grip Adhesive for Vinyl

- Smooth Substrates; Coverage is approximately 160 – 190 Square Feet



- VOC Information; 0 g/L

- FloorScore Certified
- LEED Compliant
- Moisture Requirements:
 - ASTM F 1869, Calcium Chloride: 7.0 Lbs
 - ASTM F 2170, Relative Humidity: 85%
 - pH: 11 or less

Flexco 16/86 Multi-Performance Tile & Tread Adhesive

- Smooth Porous Substrates, 1/16" x 1/16" x 1/16" Flat V Notch; Coverage is approximately 125 – 150 Square Feet / gallon



- Rough Porous Substrates, 1/16" x 1/16" x 1/16" Square Notch; Coverage is approximately 100 – 125 Square Feet / gallon



- Smooth Non-Porous Substrates, 1/32" x 1/16" x 1/32" U Notch; Coverage is approximately 150 – 175 Square Feet / gallon



- VOC Information; <13 g/L
- Green Label Plus Certification
- CHPS Compliant
- LEED Compliant
- Moisture Requirements:
 - ASTM F 1869, Calcium Chloride: 4.0 Lbs
 - ASTM F 2170, Relative Humidity: 70%
 - pH: 9 or less

Flexco 77 Solvent Free Epoxy Adhesive

- Smooth Substrates, 1/32" x 1/16" x 1/32" U Notch; Coverage is approximately 150 – 175 Square Feet / gallon



- Rough Substrates, 1/16" x 1/16" x 1/16" Flat V; Coverage is approximately 125 – 150 Square Feet / gallon



- VOC Information; Part A: .13 g/L, Part B: 2.4 g/L, 1.211g/L when mixed
- Green Label Plus Certification
- CHPS Compliant
- LEED Compliant
- Moisture Requirements:
 - ASTM F 1869, Calcium Chloride: 5.0 Lbs
 - ASTM F 2170, Relative Humidity: 75%
 - pH: 9 or less

7. PRODUCT MAINTENANCE

- Neutral pH cleaners
- Initial scrubbing and buff 48 Hours after installation
- Regular scrubbing and buffing as needed
- Daily sweep & Vacuum to remove loose dirt & debris

8. SAMPLES

Obtain Samples calling Flexco Customer Service or by visiting www.flexcofloors.com.

9. AVAILABILITY AND COST

Products are available through Flexco distributors. Contact Flexco Customer Service or visit www.flexcofloors.com for a list of distributors.

10. LIMITED WARRANTY

Limited One (1) Year Manufacturers Warranty
 Limited Ten (10) Year Wear Warranty

Refer to Flexco WoodTones Premium Wood Vinyl Plank Installation or Maintenance documentation for any additional detailed information.

www.flexcofloors.com/technicalsupport/index.html

