

1. PRODUCT NAME**Base Sculptures™ Wall Base, 4.5"****2. COMPANY INFORMATION**

Flexco Corporation

1401 East 6th Street

Tuscumbia, AL, USA 35674

Phone: (256) 383-7474; (800) 633-3151

Fax: (256) 381-0322; (800) 346-9075

Email: info@flexcofloors.com, technical@flexcofloors.comInternet: www.flexcofloors.com**3. PRODUCT DESCRIPTION**

ASTM F 1861, Type TP, Group 1, Style D

Thermoplastic Rubber Formulation designed to meet or exceed the above-mentioned standard specification for Resilient Wall Base.


Pre-Mitered Inside and Outside corners are available with a nominal 3" return. Inside and Outside corner blocks are available as well.

SC-XX, 4 1/2"



3/8"

Available in 40' Coils

Color Sample:Attach Color
Sample Here**4. TECHNICAL DATA****ASTM E 84 (NFPA 255)** - Class B**ASTM E 648 (NFPA 253)** - Class 1**ASTM E 662 (NFPA 258)** - Passes**ASTM F 1861**- Meets or exceeds the requirements for heat & light aging, chemical resistance and dimensional stability**5. LEED INFORMATION**

May contribute to LEED® CI and NC credits MR 4, MR 5 and MR 6. For detailed LEED information, see

flexco.ecoscorecard.com**6. INSTALLATION**

Maintain the installation area, wall base, and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation. Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood, concrete and masonry that are clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, nonporous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Refer to Base Sculptures Wall Base Installation instructions for detailed information.

7. ADHESIVES**Flexco 106 Wall Base Adhesive**

- Apply with 1/8" square notch trowel, adhesive spreader or disposable nozzle
- Coverage: approximately 175 linear feet of 4 1/2" Base Sculptures
- Contains Anti-Microbial Protection
- VOC's: < 1 g/L of material & coating

8. PRODUCT MAINTENANCE

Refer to Flexco Base Sculptures Wall Base Maintenance Information for detailed instructions

9. AVAILABILITY AND COSTProducts are available through Flexco distributors. Contact Flexco Customer Service or visit www.flexcofloors.com for a list of distributors.**10. LIMITED WARRANTY**

Limited One (1) Year Warranty

