

1. PRODUCT NAME

Wallflowers Wall Base, 4.5" Cove


2. COMPANY INFORMATION

Flexco Corporation
 1401 East 6th Street
 Tuscumbia, AL, USA 35674
 Phone: (256) 383-7474; (800) 633-3151
 Fax: (256) 381-0322; (800) 346-9075
 Email: info@flexcofloors.com, technical@flexcofloors.com
 Internet: www.flexcofloors.com

3. PRODUCT DESCRIPTION


ASTM F 1861, Type TS, Group 1, Style B
 Thermoset Rubber Formulation designed to meet or exceed the above-mentioned standard specification for Resilient Wall Base. Outside corners are available with a nominal 3" return.

WF-XX, 4.5" Cove



Available in 48" Lengths and 120' Coils

Color Sample:



4. TECHNICAL DATA

ASTM E 84 (NFPA 255) - Class B
ASTM E 648 (NFPA 253) - Class 1
ASTM E 662 (NFPA 258) - Passes
ASTM F 1861- Meets or exceeds the requirements for heat & light aging, chemical resistance and dimensional stability

5. LEED INFORMATION

May contribute to LEED® CI and NC credits MR 5 and MR 6. For detailed LEED information, see flexco.ecoscorecard.com

6. INSTALLATION

Maintain the installation area, wall base, and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation. Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood, concrete and masonry that are clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, nonporous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Refer to Wallflowers Wall Base Installation instructions for detailed information.

7. ADHESIVES

Flexco 106 Wall Base Adhesive

- Apply with 1/8" square notch trowel, adhesive spreader or disposable nozzle
- Coverage: approximately 200 linear feet of 4 1/2" Wallflowers Wall Base
- Contains Anti-Microbial Protection
- VOC's: < 1 g/L of material & coating

8. PRODUCT MAINTENANCE

Refer to Flexco Wallflowers Wall Base Maintenance Information for detailed instructions

9. AVAILABILITY AND COST

Products are available through Flexco distributors. Contact Flexco Customer Service or visit www.flexcofloors.com for a list of distributors.

10. LIMITED WARRANTY

Limited One (1) Year Warranty

