

### 1. PRODUCT NAME

**WoodTones™ Premium Wood Vinyl Plank**

### 2. COMPANY INFORMATION

Flexco Corporation  
 1401 East 6<sup>th</sup> Street  
 Tuscumbia, AL, USA 35674  
 Phone: (256) 383-7474; (800) 633-3151  
 Fax: (256) 381-0322; (800) 346-9075  
 Email: [info@flexcofloors.com](mailto:info@flexcofloors.com), [technical@flexcofloors.com](mailto:technical@flexcofloors.com)  
 Internet: [www.flexcofloors.com](http://www.flexcofloors.com)

### 3. PRODUCT DESCRIPTION

ASTM F 1700, Class III, Type B  
 Printed film vinyl tile with a solid vinyl tile embossed wear layer designed to meet or exceed the above-mentioned standard specification for Solid Vinyl Tile.


WT-XXX, 3" x 36" Straight Edge



WT-XXXBEV, 3" x 36" Beveled Edge



**Color Sample:**



### 4. TECHNICAL DATA

- ASTM F 1700 - Solid Vinyl Tile; Class III, Type B
- ASTM E 648 (NFPA 253), Critical Radiant Flux - Class 1
- ASTM E 662 (NFPA 258), Smoke Density - Passes
- ASTM F 925, Chemical Resistance - Passes
- ASTM D 2047, Slip Resistance - > 0.50
- ASTM F 970, Static Load - 250 PSI; Modified 300 PSI
- ASTM F 1515, Light Stability - Passes
- ASTM F 3389, Abrasion Resistance - Excellent
- ASTM G 21 - Excellent Resistance

### 5. LEED INFORMATION

May contribute to LEED® CI and NC credits MR 4, MR 5 and MR 6. For detailed LEED information, see [flexco.ecoscorecard.com](http://flexco.ecoscorecard.com)

### 6. INSTALLATION

Maintain the installation area, flooring and adhesive between 65° F and 85° F for at least 48 hours before installation, during installation, and after the installation. Perform proper moisture testing as required. All substrates must be clean, smooth, permanently dry, flat, and structurally sound. The substrate must be free of moisture, dust, sealers, paint, curing compounds, parting agents, residual adhesives, adhesive removers, hardeners, resinous compounds, solvents, wax, oil, grease, asphalt, gypsum compounds, alkaline salts, excessive carbonation or laitance, mold, mildew, any other extraneous coatings, films, materials and all other foreign matter which might interfere/restrict proper adhesive bonding. In renovation or remodel work, remove all existing adhesive residue so that 100% of the overall area of the original subfloor/substrate is exposed. Refer to WoodTones Premium Wood Vinyl Plank Installation instructions for detailed information.

### 7. ADHESIVES (Leave Only Specified Adhesive)

#### Flexco Spray-Grip Adhesive for Vinyl

- Smooth Substrates; Coverage is approximately 160 – 190 Square Feet



- VOC Information; 0 g/L
- FloorScore Certified
- LEED Compliant
- Moisture Requirements:
  - ASTM F 1869, Calcium Chloride: 7.0 Lbs
  - ASTM F 2170, Relative Humidity: 85%
  - pH: 11 or less

#### Flexco 16/86 Multi-Performance Tile & Tread Adhesive

- Smooth Porous Substrates, 1/16" x 1/16" x 1/16" Flat V Notch; Coverage is approximately 125 – 150 Square Feet / gallon



- Rough Porous Substrates, 1/16" x 1/16" x 1/16" Square Notch; Coverage is approximately 100 – 125 Square Feet / gallon



- Smooth Non-Porous Substrates, 1/32" x 1/16" x 1/32" U Notch; Coverage is approximately 150 – 175 Square Feet / gallon



- VOC Information; <13 g/L
- Green Label Plus Certification
- CHPS Compliant
- LEED Compliant
- Moisture Requirements:
  - ASTM F 1869, Calcium Chloride: 4.0 Lbs
  - ASTM F 2170, Relative Humidity: 70%
  - pH: 9 or less

**Flexco 77 Solvent Free Epoxy Adhesive**

- Smooth Substrates, 1/32" x 1/16" x 1/32" U Notch; Coverage is approximately 150 – 175 Square Feet / gallon



- Rough Substrates, 1/16" x 1/16" x 1/16" Flat V; Coverage is approximately 125 – 150 Square Feet / gallon



- VOC Information; Part A: .13 g/L, Part B: 2.4 g/L, 1.211g/L when mixed
- Green Label Plus Certification
- CHPS Compliant
- LEED Compliant
- Moisture Requirements:
  - ASTM F 1869, Calcium Chloride: 5.0 Lbs
  - ASTM F 2170, Relative Humidity: 75%
  - pH: 9 or less

**8. PRODUCT MAINTENANCE**

Refer to Flexco WoodTones Premium Wood Vinyl Plank Maintenance Information for detailed instructions

**9. AVAILABILITY AND COST**

Products are available through Flexco distributors. Contact Flexco Customer Service or visit [www.flexcofloors.com](http://www.flexcofloors.com) for a list of distributors.

**10. LIMITED WARRANTY**

Limited One (1) Year Manufacturers Warranty  
 Limited Ten (10) Year Wear Warranty

