

Rubber Stair Tread Architectural Specification

COMPANY INFORMATION

Flexco Corporation
1401 East 6th Street
Tuscumbia, AL, USA 35674
Telephone: (256) 383-7474; (800) 633-3151
Facsimile: (256) 381-0322; (800) 346-9075
Email: info@flexcofloors.com, technical@flexcofloors.com
Internet: www.flexcofloors.com
Sweet's Catalog: 09650/FLE; Buyline 0254; www.sweets.com

ARCHITECTURAL SPECIFICATION

RUBBER STAIR TREADS

FLEXCO Rubber Stair Treads manufactured by FLEXCO, Tuscumbia, AL 35674. Rubber Stair Treads shall be constructed of first-quality materials and shall be free from imperfections. Treads shall be (120, 500, 550, 600, 650 SN, 650 RN, 701, 701E, 800, 1701, 1900) Series Stair Treads in the color stated. Treads shall be free from objectionable odors, blisters, cracks and other imperfections, which will detract from the serviceability and appearance of the treads. Treads shall conform to ASTM F 2169, Type TS, and shall contain no asbestos fiber. Treads shall be (36", 42", 48", 54", 60", 72", 84", 96", 108") in length. Install Flexco Rubber Stair Treads with recommended FLEXCO adhesives including #36 Epoxy Nose Caulking Compound.

VISUALLY IMPAIRED RUBBER STAIR TREADS

FLEXCO Rubber Stair Treads manufactured by FLEXCO, Tuscumbia, AL 35674. Rubber Stair Treads shall be constructed of first-quality materials and shall be free from imperfections. Treads shall be (130, 170, 575, 585, 675, 776, 776E, 875, 1776, 1975) Series Stair Treads in the color stated. Treads shall be free from objectionable odors, blisters, cracks and other imperfections, which will detract from the serviceability and appearance of the treads. Treads shall conform to ASTM F 2169, Type TS, and shall contain no asbestos fiber. Treads shall be (36", 42", 48", 54", 60", 72", 84", 96", 108") in length. Install Flexco Rubber Stair Treads with recommended FLEXCO adhesives including #36 Epoxy Nose Caulking Compound.